

LIDO



Characteristics	Test method	
Innehåll / Composition		100% Polyester
Vikt / Weight		480
Martindale	SS-EN ISO 12947-2	106 700
Pilling	SS-EN ISO 12945-2	4(5)
Ljusäkthet/ Colour fastness to light	SS-EN ISO 105-B02	6 (8)
Torrnidning / Colour fastness to rubbing dry	SS-EN 105-X12 + SS-EN ISO 105-D02 + SS 182410	4-5 (5)
Våtgnidning / Colour fastness to rubbing wet	SS-EN ISO 105-C06	4-5 (5)
Färghärdighet mot vattentvätt / Colour fastness to waterwash	SS-EN ISO	4-5
Färghärdighet mot kemtvätt / Colour fastness to dry cleaning	SS-EN ISO 105-D01	4-5
Färghärdighet mot Vattenfläckning / Colour fastness to water spotting	SS – ISO 105-E16	4-5
Färghärdighet mot svett / Colour fastness to sweat	SS-EN ISO 105-E04	4-5
Sömskridning (varp och väft) /Seam slippage	SS-EN ISO 105-B02 Alt. SS-EN 13936-3	2mm (warp and weft)
Brandtest / Fire test		EN 1021-1
Tvättinstruktion / Washing instructions		60° el. kemtvätt
Krympning/Shrinkage		Length -1,5%, Width -2%

Signatur: