

SHERWIN-WILLIAMS

SAFETY DATA SHEET

Date of issue/ Date of revision : 2016-11-02.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Laqvin Prime DI
Product code : ED1401-9902
Product type : Waterborne Pigmented Primer

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use Industrial PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) and Painting-related materials.

1.3 Details of the supplier of the safety data sheet

Sherwin-Williams Sweden AB
Box 2016, SE-195 02 Märsta, SWEDEN
Tel: +46 (0)381 261 00
Fax: +46 (0)381 261 95
info.acroma@sherwin.com

e-mail address of person responsible for this SDS : sweden.regulatory@sherwin.com

National contact

Serbia : Sherwin-Williams Balkan SRL
CHISODA, DN.59 KM 8+ 550 M stanga OP 1, CP 513
RO-300 024 TIMISOARA, Romania
Phone: +40 256 420 320
Fax: +40 256 420 326
sales.balkan@sherwin.com

Bosnia and Herzegovina : Sherwin-Williams Balkan SRL
CHISODA, DN.59 KM 8+ 550 M stanga OP 1, CP 513
RO-300 024 TIMISOARA, Romania
Phone: +40 256 420 320
Fax: +40 256 420 326
sales.balkan@sherwin.com

Macedonia : Sherwin-Williams Balkan SRL
CHISODA, DN.59 KM 8+ 550 M stanga OP 1, CP 513
RO-300 024 TIMISOARA, Romania
Phone: +40 256 420 320
Fax: +40 256 420 326
sales.balkan@sherwin.com

Russian Federation : ZAO Sherwin-Williams
22, 1-ja Konnaja Lahta str.
pos. Olgino
197229 St. Petersburg
Russia
Phone: +7 812 334 97 54
info@beckeracroma.ru

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Rep. of Belarus : Sherwin-Williams BEL
Office 12, 12; building ODO "Dinko"
Ozertso vill. BY-223021
P.O. Box 34
Minsk District
Republic of Belarus
Phone: +375 17 507 67 74
info@beckeracroma.by

Ukraine : LTD Sherwin-Williams Ukraine
5 Solomenskaya str.
office 402
03110 Kiev
Phone: +38 050 143 23 43
yuliya.sobol@sherwin.com

China : Sherwin-Williams (Shanghai) Ltd.
188 Wuxiang Road, Xu Hang Town
Jiading, Shanghai 201808
Phone: +86 21 59552882
info@beckeracroma.com.cn

Thailand : Sherwin-Williams (Thailand) Co., Ltd.
700/254 M00 1 Amata Nakorn
Industrial Estate
Tambol Bankao
Amphur
Panthong
TH-20160 Chonburi
Thailand
Phone: +66 38 465 220
becker.th@sherwin.com

Vietnam : Sherwin-Williams (Vietnam) Ltd.
Hoa Lan block
Thuan Giao ward
Thuan An town
Binh Duong Province
Vietnam
Phone: +84 65 3747343
info@sherwin.com.vn

Malaysia : Sherwin-Williams Malaysia Sdn Bhd
PLO 572 Jalan Keluli 10
Kawasan Perindustrian
Pasir Gudang , Johor 81700
Phone: +60 7 252 9000
enquiry@sherwin.com.my

New Zealand : Wood Finishing Supplies Ltd.
P.O. Box 58-467
Botany
Manukau 2163, Auckland
New Zealand
Phone: +64 9 917 1310
aaroni@wfsupplies.co.nz

1.4 Emergency telephone number

Telephone number : Sherwin-Williams Sweden, +46 (0)381 262 59, +46 (0)381 262 34, +46 (0)381 262 75

Hours of operation : Monday-Friday 08.00-16.30 CET

Emergency telephone number of official advisory body :

Australia: 000	Belarus: 103	Canada: 911	China: 120	Hong Kong: 999
Indonesia: 118/119	Malaysia: 999	New Zealand: 111	Philippines: 117	Russia: 03
Taiwan: 119	Thailand: 1669	Ukraine: 103/112	Vietnam: 115	USA: 911
Serbia: 94/112	Bosnia-Herzegovina: 124	Macedonia: 194		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : Avoid release to the environment.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label elements : Contains 2,4,7,9-tetramethyldec-5-yne-4,7-diol and 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

2.3 Other hazards

Other hazards which do not result in classification : Not available

SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture

Product/ingredient name	Identifiers	%	<u>Classification</u> Regulation (EC) No. 1272/2008 [CLP]	Type
China clay/C.I. Pigment White 19	EC: 310-194-1 CAS: 1332-58-7	12,5-15	Not classified.	[2]
Talc/C.I. Pigment White 26	EC: 238-877-9 CAS: 14807-96-6	7-10	Not classified.	[2]
Titanium dioxide/C.I. Pigment White 6	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	7-10	Not classified.	[2]
Butyl glycol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	1-2,5	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
3-Iodo-2-propynyl butylcarbamate	EC: 259-627-5 CAS: 55406-53-6	0,1-0,5	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	[1]
2,4,7,9-Tetramethyl-5-decyne-4,7-diol	REACH #: 01-2119954390-39 EC: 204-809-1 CAS: 126-86-3	0,1-0,5	Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above.	[1]

SECTION 3: Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | |
|-----------------------------------|---|
| General | : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice. |
| Eye contact | : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 5 minutes, keeping eyelids open. |
| Inhalation | : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. |
| Skin contact | : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. |
| Ingestion | : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of 1272/2008 and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 3-iodo-2-propynyl butylcarbamate, 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|----------------------------|---|
| Notes to physician | : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : No specific treatment.
Not available |

See toxicological information (Section 11)

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|---------------------------------------|--|
| Suitable extinguishing media | : Recommended: alcohol-resistant foam, CO ₂ , powders, water spray. |
| Unsuitable extinguishing media | : Do not use water jet. |

5.2 Special hazards arising from the substance or mixture

- | | |
|--|--|
| Hazards from the substance or mixture | : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. |
|--|--|

SECTION 5: Firefighting measures

Hazardous thermal decomposition products : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

5.3 Advice for firefighters

Special protective actions for fire-fighters : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

SECTION 6: Accidental release measures

Due to the organic solvents content of the preparation:

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

6.3 Methods and materials for containment and cleaning up : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Preferably clean with a detergent. Avoid using solvents.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling : Due to the organic solvents content of the preparation:

Prevent the creation of flammable or explosive concentrations of vapors in air and avoid vapor concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Put on appropriate personal protective equipment (see Section 8).

Never use pressure to empty. Container is not a pressure vessel.

Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Information on fire and explosion protection

Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapors in all cases. In such circumstances, they should wear a compressed-air-fed respirator during the spraying process and until the particulate and solvent vapor concentrations have fallen below the exposure limits.

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidizing agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Do not store below the following temperature: 5°C (41°F).

Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.

Due to the organic solvents content of the preparation:

Keep container tightly closed.

Keep away from sources of ignition. No smoking. Prevent unauthorized access.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

Recommendations : Not available

Industrial sector specific solutions : Not available

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Europe	
Kaolin	ACGIH TLV (United States, 4/2014). TWA: 2 mg/m ³ 8 hour(s). Form: Respirable fraction
Talc	ACGIH TLV (United States, 4/2014). TWA: 0,1 f/cc 8 hour(s). Form: Respirable fibers: length greater than 5 µm; aspect ratio equal to or greater than 3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination.
Titanium dioxide	ACGIH TLV (United States, 4/2014). TWA: 10 mg/m ³ 8 hour(s).
2-Butoxyethanol	EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values STEL: 246 mg/m ³ 15 minute(s). STEL: 50 ppm 15 minute(s). TWA: 98 mg/m ³ 8 hour(s). TWA: 20 ppm 8 hour(s).

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Derived effect levels

Product/ingredient name	Type	Exposure	Value	Population	Effects
titanium dioxide	DNEL	Long term Inhalation	10 mg/m ³	Workers	Local
2-butoxyethanol	DNEL	Short term Dermal	89 mg/kg bw/day	Workers	Systemic
	DNEL	Short term Inhalation	135 ppm	Workers	Systemic
	DNEL	Short term Inhalation	50 ppm	Workers	Local
	DNEL	Long term Dermal	75 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	20 ppm	Workers	Systemic
	DNEL	Short term Dermal	44,5 mg/kg bw/day	Consumers	Systemic

SECTION 8: Exposure controls/personal protection

	DNEL	Short term Inhalation	426 mg/m ³	Consumers	Systemic
	DNEL	Short term Oral	13,4 mg/kg bw/day	Consumers	Systemic
	DNEL	Short term Inhalation	123 mg/m ³	Consumers	Local
	DNEL	Long term Dermal	38 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	49 mg/m ³	Consumers	Systemic
	DNEL	Long term Oral	3,2 mg/kg bw/day	Consumers	Systemic

Predicted effect concentrations

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
titanium dioxide	PNEC	Soil	100 mg/kg	-
	PNEC	Marine water sediment	100 mg/kg	-
	PNEC	Fresh water sediment	1000 mg/kg	-
	PNEC	Marine	1 mg/kg	-
2-butoxyethanol	PNEC	Fresh water	0,127 mg/kg	-
	PNEC	Fresh water	8,8 mg/l	-
	PNEC	Marine	0,88 mg/l	-
	PNEC	Sewage Treatment Plant	463 mg/l	-
	PNEC	Fresh water sediment	34,6 mg/kg dwt	-
	PNEC	Marine water sediment	3,46 mg/kg dwt	-
	PNEC	Soil	2,8 mg/kg dwt	-
	PNEC			

8.2 Exposure controls

Appropriate engineering controls : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Use safety eyewear designed to protect against splash of liquids.

Skin protection

Hand protection : Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Gloves : Gloves must be worn for all work that may result in soiling. Wear suitable gloves tested to EN374. Recommended: Butyl gloves. For specific applications, it is recommended to check the chemical resistance of the protective gloves mentioned above with the glove manufacturer. Do not wear the same gloves for other work. The recommendation for the type or types of glove to use when handling this product is based on information from the following source: European Solvents Industry Group (ESIG) & AnsellPro. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection : Personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Recommended Environmental exposure controls : particulate filter, P2-P3
: Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid.
Color	: White
Odor	: Faint odor.
Odor threshold	: Not available (Not tested)
pH	: 7 to 9
pH	: Not applicable. (non-aqueous preparation)
Melting point/freezing point	: Not available (Not tested)
Initial boiling point and boiling range	: Not available (Not tested)
Flash point	: Closed cup: 101°C [ASTM 6450]
Evaporation rate	: Not available (Not tested)
Flammability (solid, gas)	: Not available (Not tested)
Burning time	: Not available (Not tested)
Burning rate	: Not available (Not tested)
Upper/lower flammability or explosive limits	: Lower : 1.1%-v/v, upper : 12.7%-v/v.
Vapor pressure	: Not available (Not tested)
Vapor density	: Not available (Not tested)
Relative density	: 1,3 g/cm ³
Solubility(ies)	: Not available (Not tested)
Partition coefficient: n-octanol/water	: Not available (Not tested)
Auto-ignition temperature	: Not available (Not tested)
Decomposition temperature	: Not available (Not tested)
Viscosity	: Not available
Explosive properties	: Under normal conditions of storage and use, hazardous reactions will not occur.
Oxidizing properties	: Under normal conditions of storage and use, hazardous reactions will not occur.
VOC content	

g/l : 22
% : 1,7

Dry content (%) : 50

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see section 7).
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products.
10.5 Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the preparation itself. The preparation has been assessed following the conventional method of 1272/2008 and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 3-iodo-2-propynyl butylcarbamate, 2,4,7,9-tetramethyldec-5-yne-4,7-diol. May produce an allergic reaction.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-Butoxyethanol	LC50 Inhalation Gas. LD50 Dermal	Rat Rabbit	450 ppm 220 mg/kg	4 hours -
3-iodo-2-propynyl butylcarbamate	LD50 Oral LD50 Dermal	Rat Rabbit	250 mg/kg >2000 mg/kg	- -
	LD50 Oral	Rat	1056 to 1795 mg/kg	-
2,4,7,9-tetramethyldec-5-yne-4,7-diol	LC50 Inhalation Dusts and mists LD50 Dermal	Rat Rabbit	>20000 mg/m3 >100 mg/kg	1 hours -
	LD50 Oral	Rat	>500 mg/kg	-

Acute toxicity estimates

Route	ATE value
Oral Dermal Inhalation (gases) Inhalation (dusts and mists)	36121,9 mg/kg 79468,3 mg/kg 325097,5 ppm 156,2 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Talc	Skin - Mild irritant	Human	-	-	-
Titanium dioxide	Skin - Mild irritant	Human	-	-	-
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	-	-
	Eyes - Severe irritant	Rabbit	-	-	-
	Skin - Mild irritant	Rabbit	-	-	-
2,4,7,9-tetramethyldec-5-yne-4,7-diol	Eyes - Severe irritant	Rabbit	-	-	-
	Skin - Mild irritant	Rabbit	-	-	-

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
3-iodo-2-propynyl butylcarbamate	Category 1	Not determined	Not determined

Aspiration hazard

Not available.

Other information : Not available

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of 1272/2008 and is not classified as dangerous for the environment.

Product/ingredient name	Result	Species	Exposure
Titanium dioxide	Acute LC50 5,5 ppm Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling) - <24 hours	48 hours
	Acute LC50 >1000000 ug/L Marine water	Fish - Fundulus heteroclitus	96 hours
	Chronic NOEC 1 ppm Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling) - <24 hours	48 hours
2-Butoxyethanol	Acute EC50 >1000 mg/L Fresh water	Daphnia - Daphnia magna - <24 hours	48 hours
	Acute LC50 800000 to 1000000 ug/L Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 1250000 ug/L Marine water	Fish - Menidia beryllina - 40 to 100 mm	96 hours
3-iodo-2-propynyl butylcarbamate	Chronic NOEC 1000 mg/L Fresh water	Daphnia - Daphnia magna - <24 hours	48 hours
	Acute EC50 0,5 mg/l	Algae	96 hours
	Acute LC50 500 ppb Fresh water	Crustaceans - Hyalella azteca - 2 to 9 days	48 hours
	Acute LC50 0,64 mg/l	Daphnia	48 hours
	Acute LC50 40 to 55 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 67 to 79 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 0,1 mg/l	Fish	96 hours

12.2 Persistence and degradability

Conclusion/Summary : Not available

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-Butoxyethanol	-	-	Readily
3-iodo-2-propynyl butylcarbamate	-	-	Readily
2,4,7,9-tetramethyldec-5-yne-4,7-diol	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2-Butoxyethanol	0,83	-	low
3-iodo-2-propynyl butylcarbamate	2,4	4,4	low
2,4,7,9-tetramethyldec-5-yne-4,7-diol	3,61	120	high

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available

Mobility : Not available

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

European waste catalogue (EWC) : 08 01 12 waste paint and varnish other than those mentioned in 08 01 11

Hazardous waste : No.

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Ensure packaging is completely empty before recycling. Dispose of uncured residues in the same way as the product itself.

Plastic. EWC 15 01 02 plastic packaging

Metal. EWC 15 01 04 metallic packaging

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
14.6 Special precautions for user	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Additional information	-	-	-

SECTION 14: Transport information

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

Europe inventory : Not determined.

Black List Chemicals : Not listed

Priority List Chemicals : Not listed

Integrated pollution prevention and control list (IPPC) - Air : Not listed

Integrated pollution prevention and control list (IPPC) - Water : Not listed

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

International regulations

Chemical Weapons Convention List Schedule I Chemicals : Not listed

Chemical Weapons Convention List Schedule II Chemicals : Not listed

Chemical Weapons Convention List Schedule III Chemicals : Not listed

15.2 Chemical Safety Assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

CEPE code : 2

Indicates information that has changed from previously issued version.

SECTION 16: Other information

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Full text of abbreviated H statements

: H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H372 Causes damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

: Acute Tox. 3, H331 ACUTE TOXICITY: INHALATION - Category 3
Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4
Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4
Acute Tox. 4, H332 ACUTE TOXICITY: INHALATION - Category 4
Aquatic Acute 1, H400 AQUATIC TOXICITY (ACUTE) - Category 1
Aquatic Chronic 1, H410 AQUATIC TOXICITY (CHRONIC) - Category 1
Aquatic Chronic 3, H412 AQUATIC TOXICITY (CHRONIC) - Category 3
Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2, H319 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Skin Irrit. 2, H315 SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1
STOT RE 1, H372 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1

Date of printing : 2017-02-13.

Date of issue/ Date of revision : 2016-11-02.

Date of previous issue : 2016-10-12.

Version : 2.02

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.